

RAILWAY VEHICLE ACCESS SOLUTIONS

From lifting jacks to train traversers, CoxGomyl Railway maintenance capabilities include a full range of engine and carriage lifting equipment, all built to European manufacturing standards. All products utilise the latest advances in electrical and mechanical design and materials. These extremely powerful machines are capable of very high loading, which is generally measured in tonnes. (indicated as Tm)

Like all of the company's renowned building maintenance units (BMUs), CoxGomyl Railway products are accredited to the international quality management system EN-ISO 9001: 2000, ensuring customers enjoy the peace of mind that all products are designed to the most stringent quality standards.

Through the application of technical knowledge gained through over 50 years of designing and manufacturing heavily engineered lifting equipment, CoxGomyl has developed a wide range of innovative railway maintenance equipment that has been proven in the workshops of leading railway companies around the world.



Lifting Jacks & Lifting Portals

Lifting jacks and portals provide a means of jacking engines and carriages enabling easy access for maintenance and repair.

- Mechanical spindle drives with abrasion control on main nut
- Synchronized movement control of 2 -16 units
- Adjustable height supports with loading control
- Load capacity:
 Jack: up to 35 Tm/ jack

 Portal: up to 2x35 Tm/ portal.



Maintenance Platforms

Either wall bottom or roof mounted, maintenance platforms provide a means to access all sides and the roof of vehicles without obstructing the ground level.

- Mechanical and electrical interlock of access doors
- Safety sensors and control interlock
- Mechanical over speed control for descent
- Backup manual descent device
- Lifting capacity: up to 240Kg
- · Lifting height: up to 5m



Bogie Inspection Stand

This stand provides safe, close access to the bogie for inspection. The bogie is pivot mounted and the stand can be lifted.

- Load capacity up to 4 Tm/ stand
- Adjustable height supports with loading control.

Mobile Access Platform

The platform provides safe and comfortable side and roof access, applicable to narrow passages.

- Sliding platform for gap bridging
- Trip-bar for vehicle protection
- Secured battery drive system
- Load capacity: up to 240Kg
- Lifting height: up to 5.5m



This drop system provides for the safe interchange of bogies and wheel sets without the necessity to lift the vehicles.

- · Dimensions as per request
- Maximum load capacity up to 75 Tm
- Mechanical lifting spindle drive x 4, synchronized
- Controlled position for all movements
- Carbody supports
- Traversing and elevation control by PLC's.



These innovative traversing devices offer a convenient way to move heavy loads.

- Load capacity up to 30 Tm
- Pendant control
- · Synchronized movement control.
- Lifting height: up to 2m

Rail Drop System

For elevated track systems in the depot the rail drop system, provides access to the underside of the carriage by lowering the tracks, allowing the wheel set, motor and air conditioning units to be inspected, maintained and replaced.

- Mechanical lifting spindle drive x 4, synchronized
- Dual safety control circuits for all movements, services and emergency stops
- · Signal systems for vehicles moving in and out
- Possibility to incorporate scissor lift platforms between tracks to assist in component replacement
- Lifting capacity: up to 12Tm
- Lifting range: up to 1.2m

Train Traversers

Traversers are designed to transport heavy-duty rail vehicles between depots and/or different tracks

- · Capacity and dimensions as per customer request
- Visual, acoustic and signaling during traversing movement
- Dual control signal from the cabin or by radio control.













Common Safety Features

- All leveling and synchronized movement carried out by encoders and PLCs
- Lifting systems utilize fail safe mechanical spindle drives coupled with gear-motors and double safety nut system. Abrasion control in main nut
- Dual safety control circuits for all movements, service and emergency stops
- Flashing and audible movement alarms
- Guard rails and safety measures are in accordance with European standards EN 85237

- Overload devices and alarms
- Overspeed brake, for the mobile access platforms
- Interlock devices to prevent the operations under the overhead power lines
- All welding is carried out in accordance with the most stringent standards: EN 729-2, EN 15614-1.
 All welders are certified to UNE EN 287-1
- Equipment complies with the current European Machinery Directive: 2006/42/EC
- Equipment complies with European standard for electrical equipment of machines: EN 60204-1.

Head Office

182 Normanby Road Southbank, Vic 3006, Australia Phone: +61 3 9673 4444 Fax: +61 3 9673 4400 Email: headoffice@coxgomyl.com

Asia Region

Hong Kong and South China Office Flat 04A, 11th Floor, Eastern Centre 1065 King's Road, Quarry Bay Hong Kong SAR, China

Phone: +852 2802 2221 Fax: +852 2824 9626

Email: hongkong@coxgomyl.com

Central and North China Office Rm.606 Tong Sheng Tower No. 458 FuShan Road Shanghai, China 200122 Phone: +86 21 5465 2455

Fax: +86 21 6467 7507 Email: shanghai@coxgomyl.com

South East Asia Office 18 Boon Lay Way, Tradehub 21 #03-125 Singapore 609966

Phone: +65 6513 4780 Fax: +65 6425 6100

Email: singapore@coxgomyl.com

Europe Region

Western Europe and Latin America Office Calle de la Venta, no 19 28880 Meco, Madrid Spain

Phone: +34 9188 77000 Fax +34 9188 60514 Email: madrid@coxgomyl.com

United Kingdom Office 19 Schooner Park, Schooner Court, Crossways Business Park, Dartford, DA2 6NW, United Kingdom

Phone: +44 1322 221414 Fax: +44 1322 228419 Email: london@coxgomyl.com

Russia and East Europe Office 3Pl. Tverskaya Zastava, Office 240 Moscow, Russia, 125047

Phone: +7 499 250 8975 Fax: +7 499 250 2729 Email: russia@coxgomyl.com

Rest of the World (ROW) Region

Australia and NZ Office 182 Normanby Road Southbank, VIC 3006, Australia

Phone: +61 3 9673 4444 Fax: +61 3 9673 4400

Email: melbourne@coxgomyl.com

Middle East Regional Office PO Box 33654 Dubai. UAE

Phone: +971 4 511 8200 Fax: +971 4 511 8300 <u>Email:</u> dubai@coxgomyl.com

Abu Dhabi Commerical Mussafah ME 12, Building 232, Office M1

Abu Dhabi, UAE Phone: +971 4 511 8200 Fax: +971 4 511 8300

North America Office 216 North Avenue East Cranford, NJ 07016, USA Phone: +1 908 325 6587 Fax: +1 908 967 6042 Email: usa@coxgomyl.com

coxgomyl.com

